



## Fire Alarm Circuit Breaker Accessory

### Brochure

Siemens is proud to announce the release of the Fire Alarm Circuit Breaker Accessory. This accessory, a specific padlocking device, will clearly identify the fire alarm circuit per NFPA 72 requirements.

Rather than purchasing a new Fire Alarm Circuit Breaker, this accessory can be assembled in the field for existing plug-on, bolt-on, lug-in / lug-out, DIN rail, and single pole breakers listed below:

BAF, BAFH, BE, BL, BLE, BLEH, BLF, BLH, BLHF, BQ, BQHF, BQAF, BQAFH, BQH, BQP, HBL, HBQ, HQP, MH-T, MP-AT, MP-ET, MP-GT, MP-HAT, MP-HET, MP-HGT, MP-HT, MP-MT, MP-T, QAF, QAFH, QE, QEH, QG, QP, QPF, QPH, QPHF, QT & LQ.

#### Code Specifications NFPA 72, 2010

##### Section 10.5.5.2.2

"For fire alarm systems the circuit disconnecting means shall be identified as "FIRE ALARM CIRCUIT".

##### Section 10.5.5.2.3

"For fire alarm systems the circuit disconnecting means shall have a red marking."

Catalog Number	Description
ECPLD1R	Red Padlocking Device for 1" & Twin Breakers



Siemens Industry, Inc.  
5400 Triangle Parkway  
Norcross, GA 30092

1-800-241-4453  
info.us@siemens.com

Subject to change without prior notice  
Order No. CBBR-FIRAM-0316  
Printed in USA  
All rights reserved  
© 2016, Siemens Industry, Inc.

Subject to changes and errors. The information given in this document only contains general descriptions and/or performance features which may not always specifically reflect those described, or which may undergo modification in the course of further development of the products. The requested performance features are binding only when they are expressly agreed upon in the concluded contract.

[usa.siemens.com/resiaccessories](http://usa.siemens.com/resiaccessories)